

DAUNTLESS SERIES

28' to 65'

DEEP VEE HULL MULTI-MISSION BOATS

65' Dauntless - Survey



34' Dauntless - Patrol



28' Dauntless RAM - Harbor Security



32' Dauntless - Fire/Rescue

Dauntless Class

Standard Equipment

Hull Structures

Variable deadrise bottom; 20° at transom, continuously twisting to 50° at bow.

Lifting strakes - 2 per side

Wide Chines

Radiused bow section

4 W.T. compartments, 36'-65' Models

3 W.T. compartments, 28'-32' Models
(W.T. within 6" of sheerline or cockpit floor, whichever is less)

Bulkhead drainage valves

Welded aluminum cabin floor and pilot house floor

Heavy duty "D" rub rail

Radiused transom and transom corners

Cambered decks

Rigging tube from dash to engine room

Wire tube from dash to fore peak

Wire tube from dash to lazarette

Sacrificial hull anodes

1-year Parts Limited Warranty

10-year Hull & Deck Limited Warranty



40' Dauntless for Law Enforcement



All Dauntless Models Feature Wide Chines, Lifting Strakes And Flared Bows

Hatches and Closures

Engine access hatches with heavy duty hinges, gas shocks and safety latch, for 32'-65' models

Engine room personnel access hatch and engine room ladder, 32'-65' models

Cabin floor access cover for bilge inspection

Auxiliary machinery space service access

Aluminum walking flats in:

Engine space in 28'-65'

Auxiliary machinery space in 32'-65'

Lazarette/steering gear space in 32'-65'
(Optional)



40' Dauntless For Patrol

Dauntless Specifications

Length	28' (8.5m)	32' (9.7m)	36' (10.9m)	40' (12.2m)	42' (12.8m)	44' (13.4m)	48' (14.6m)
Beam Ex-Guard.....	10' 5" (3.2m)	11' 7" (3.5m)	12' (3.7m)	13' 6" (4.1m)	13' 6" (4.1m)	13' 6" (4.1m)	14' 6" (4.4m)
Beam Overall	10' 10" (3.3m)	12' (3.7m)	13' 2" (4.0m)	14' (4.3m)	14' (4.3m)	14' (4.3m)	15' (4.6m)
Draft (Inboard Models).....	N/A	3' 2" (0.96m)	3' 8" (1.1m)	4' 4" (1.3m)	4' 4" (1.3m)	4' 6" (1.4m)	4' 6" (1.4m)
Displacement (Lbs.).....	9,000	12,000	18,000	27,000	28,000	29,000	31,000
(kg)	(4,086 kg)	(5,448 kg)	(8,172 kg)	(12,258 kg)	(12,712 kg)	(13,166 kg)	(14,074 kg)
Engine Size - Twin.....	to 600	to 850	to 850	to 1300	to 1300	to 1300	to 1300
Bottom - Deadrise Aft	20°	20°	20°	20°	20°	20°	20°
Bottom - Deadrise Forward	48°	48°	48°	50°	50°	50°	50°

Specifications subject to change without notice.



34' Dauntless for Coastal Warfare

Fuel System

Complete with electric sender and gauge, drain plug, withdrawal fittings and shut-off valves (one per engine).

Tank size:

28'	100 gallons
32'	200 gallons
36'-42'	250 gallons
44'-48'	300 gallons
50'-55'	400 gallons
60'-65'	500 gallons

Optional larger tankage available.

Underwater Gear For Inboard Models

Air Foil shaped struts (skegs optional)

Closed shaft logs (exposed shafts optional)

Stainless steel wedge-shaped rudders with positive stops

Heavy duty rudder post framing tied to bottom and transom

Stainless steel adjustable rudder tie bar

Stainless steel shafts (Aquamet 17) sized to suit
(w/ engine installation)

Propellers - Bronze standard (w/ engine installation)

50' (15.2m)	55' (16.8m)	57' (17.4m)	60' (18.3m)	65' (19.8m)
15' 6" (4.7m)	15' 6" (4.7m)	15' 6" (4.7m)	15' 6" (4.7m)	17' 6" (5.3m)
16' (4.9m)	16' (4.9m)	16' (4.9m)	16' (4.9m)	18' (5.5m)
5' (1.5m)	5' (1.5m)	5' (1.5m)	5' (1.5m)	5' 6" (1.7m)
35,000	39,195	43,500	47,000	80,000
(15,876 kg)	(17,794 kg)	(19,731 kg)	(21,319 kg)	(36,280 kg)
to 1300	to 1300	to 1500	to 1500	to 1700
22°	22°	22°	22°	19°
50°	50°	50°	50°	52°

Standard Equipment Continued

Pilot House

- 2 – tempered safety plate clear front windows (1/4" on 28' and 32', and 3/8" on 36' to 65' models)
- 2 – 1/4" safety glass clear sliding side windows
- 2 – 1/4" safety glass tinted fixed side windows
- 2 – 1/4" safety glass tinted fixed aft bulkhead windows
- Insulated bulkhead door with dogs, padlock hasp and window
- Window screens, and additional tinting optional
- 2" insulated overhead with headliner
- 1" insulated house side walls (roof to floor) with side liners
- 1" insulated aft bulkhead with liner
- Welded aluminum pilothouse floor
- Overhead radio box
- Upholstered pilot and companion seats with slides and arms (2)
- Seat boxes, welded aluminum with open-faced storage (2)
- Seat foot rests port and starboard, folding
- Welded aluminum dash and bulkhead complete with companionway opening and high profile instrument pod
- Overhead wire way with access panel
- Window post wire ways (3)
- Rails
 - Overhead handrails (2)
 - Port dash handrail (1)
 - Aft bulkhead door rails (2)
 - P/S cabin exterior side rails (2)
 - Exterior aft house rails (2)
- Medium duty folding light mast with halyard cleat
- Optional heavy duty folding mast with radar, crosstrees and bracket mounts



42' Dauntless Pilot Boat



40' Dauntless For Coastal Patrol



32' Dauntless For Marine Mammal Support

Standard Equipment Continued

Trunk Cabin

- 1" insulated overhead with headliner
- 1" insulated cabin sides with headliner
- 2" hull insulation with hull liners
- Welded aluminum floor with bilge access opening
- Sound absorbing cabin matting, optional
- Access into auxiliary machinery space on 32'-65' models
- Companionway stairs
- Companionway handrail (1)
- Aft bulkhead wire way (for dash access)
- Wire way access hatches (2)
- Optional overhead escape hatch (20" x 20") and side ports; both available with screens

Lighting

- Side lights, Aqua Signal 41 series or equal.
- 360° anchor/navigation light mounted on folding mast
- Compartment lighting:
 - Auxiliary machinery space (1)
 - Engine room: 28' - (1)
32' - (2)
36'-65' - (3)
 - Lazarette (1)
 - Dash pod dome light (red/white)
- Overhead dome light, red/white combination: 28'-32' (2); 36'-65' (4)
- Interior console light (1)

Bilge

- High capacity bilge pumps with auto/manual feature:
 - 28' - 1 - 3700 GPH pump
 - 32' - 2 - 3700 GPH pumps
 - 36'-65' - 3 - 3700 GPH pumps

Deck Hardware

- Cleats, heavy duty, stainless steel through bolted with back-up plates - optional
 - 28'-32' - 8-12" cleats
 - 36'-65' - 8-15" cleats
- 3 Heavy duty, single post mooring bits

Steering

- Teleflex Sea Star hydraulic with flat dish stainless wheel (tilt helm optional)



36' Dauntless Crew Boat



30' Dauntless For Harbor Patrol

Navigational Aids

- Windshield wipers with pantographic arms - 2 (washer optional)
- Roof-mounted 7" manual searchlight
- Electric twin trumpet horn

Rails

- High pattern stern deck rails (two tier)
- Bow rails; select inboard or outboard rail system

Steering

- 12-Volt D.C. electrical system
- 14-Gang breaker switch panel, complete with 50 amp, main breaker, dimmer switch, horn button, and L.E.D. "On" lights

Standard Equipment Continued

Paint And Finish

Hull painted light gray (bottom paint, boot stripe and lettering optional)

Decks – slip resistant gray

Cabin and pilot house light gray

Trunk cabin roof painted slip resistant gray

Rails forward of driver flat black

Rails on house to match house color

Rails on hull to match hull color

Masts of any configuration – satin black

Window frames – black

Black dash surface and forward window posts

Bulkhead door matches cab in paint

Epoxy primer

Paint polyurethane; other grades available

Optional color schemes available

Hull anodes:

28' - 32' – (2) – 5 lbs.

36' - 42' – (4) – 5 lbs.

44' - 65' – (6) – 5 lbs.

Propulsion Options

Outboard: Single or twin

Stern Drive: Gas or diesel

Jet Drive: Gas or diesel

Inboard: Gas or diesel

Pod Drive: Diesel



30' Dauntless For Fire/Rescue



28' Dauntless For Law Enforcement



28' Dauntless For Hydrographic Survey



40' Dauntless For Drug Interdiction